

AD-A168 616

IMPROVED ADHESION OF THIN CONFORMAL FILMS TO METAL  
SURFACES(U) HARVARD UNIV CAMBRIDGE MASS DEPT OF  
CHEMISTRY K R STENARD ET AL. MAY 86 TR-85-3

1/1


UNCLASSIFIED

NO0014-83-K-0142

F/G 11/1

NL





Mr. R. S. G. F.

11/21

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

## ---ORT DOCUMENTATION PAGE

1a		1b. RESTRICTIVE MARKINGS									
2a		3. DISTRIBUTION/AVAILABILITY OF REPORT									
2b		Approved for Public release. Distribution unlimited.									
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		5. MONITORING ORGANIZATION REPORT NUMBER(S)									
3											
6a. NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION									
Harvard University		ONR									
6c. ADDRESS (City, State and ZIP Code)		7b. ADDRESS (City, State and ZIP Code)									
Department of Chemistry 12 Oxford Street Cambridge, MA 02138		Department of Navy Arlington, Virginia 22217									
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER									
ONR											
9c. ADDRESS (City, State and ZIP Code)		10. SOURCE OF FUNDING NOS									
Department of Navy Arlington, Virginia 22217		<table border="1"> <tr> <td>PROGRAM ELEMENT NO.</td> <td>PROJECT NO.</td> <td>TASK NO.</td> <td>WORK UNIT NO.</td> </tr> <tr> <td>N00014-83-K 0142</td> <td>NR 631-840</td> <td></td> <td></td> </tr> </table>		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT NO.	N00014-83-K 0142	NR 631-840		
PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT NO.								
N00014-83-K 0142	NR 631-840										
11. TITLE (Include Security Classification) "Improved Adhesion of Thin Conformal Films to Metal Surfaces"											
12. PERSONAL AUTHOR(S) K.R. Stewart, G.M. Whitesides, H.P. Godfried, I.F. Silvera											
13a. TYPE OF REPORT	13b. TIME COVERED	14. DATE OF REPORT (Yr., Mo., Day)	15. PAGE COUNT								
Preprint	FROM _____ TO _____	1983 1986									
16. SUPPLEMENTARY NOTATION											
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)									
FIELD	GROUP	SUB. GR.									
		Adhesion Promotion, Organic Thin Films, Monolayers, Gold, Polyethylene, Insulators									
19. ABSTRACT (Continue on reverse if necessary and identify by block number)											
<p>A technique is described for attaching thin, conformal, pin-hole free electrically insulating polyethylene films to flat gold surfaces (previously modified by adsorption of a monolayer of an organic disulfide) by plasma polymerization. These polyethylene films are tough enough to support the attachment of gold electrodes.</p>											
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT		21. ABSTRACT SECURITY CLASSIFICATION									
UNCLASSIFIED UNLIMITED <input checked="" type="checkbox"/> SAME AS PRTX <input type="checkbox"/> DTIC USERS <input type="checkbox"/>		Unclassified A									
22a. NAME OF RESPONSIBLE INDIVIDUAL		22b. TELEPHONE NUMBER (Include Area Code)	22c. OFFICE SYMBOL								
Kenneth J. Wynne		(202) 696-4411	NO								

OFFICE OF NAVAL RESEARCH

Contract N0014-83-K-142

Task No. NR-631-840

TECHNICAL REPORT NO. 85-3

Improved Adhesion of Thin Conformal Films to Metal Surfaces

by

Kevin R. Stewart and George M. Whitesides

Herman P. Godfried and Isaac F. Silvera


To be published in Review of Scientific Instruments

Department of Chemistry and Department of Physics  
Harvard University  
Cambridge, Massachusetts 02138

May 1986

Reproduction in whole or in part is permitted for  
any part of the United States Government

This document has been approved for public release  
and sale: its distribution is unlimited



REVISED

Improved Adhesion of Thin Conformal Organic films to Metal Surfaces

Kevin R. Stewart and George M. Whitesides

Department of Chemistry, Harvard University, Cambridge, MA 02138

and

Herman P. Godfried and Isaac F. Silvera

Department of Physics, Harvard University, Cambridge, MA 02138

**Abstract.** A technique is described for attaching thin, conformal, pin-hole free electrically insulating polyethylene films to flat gold surfaces (previously modified by adsorption of a monolayer of an organic disulfide) by plasma polymerization. These polyethylene films are tough enough to support the attachment of gold electrodes.

In recent years there has been a growing activity in the preparation of thin film devices and components on surfaces, not only for microelectronic fabrication, but also in various areas of experimental physics and chemistry. In our own case we were faced with the requirement of depositing a thin film heater and capacitor plates on a high thermal conductivity substrate for use at temperatures below 1°Kelvin. We chose copper as the substrate material. It was desirable that the components not only be electrically insulated from the substrate,<sup>1</sup> but also in very good thermal contact, for removal of heat, suggesting the use of a very thin insulating layer. An

initial attempt to precoat the copper with a few microns thick silicon oxide layer by vapor deposition failed the electrical integrity requirement due to pinholes in the insulating layer. This technique is particularly unsuitable if conformal<sup>2</sup> coatings are required on surfaces which are not flat, due to shadowing of the deposition source.

A useful technique, which can potentially provide pinhole free conformal coatings, is flow discharge polymerization, sometimes referred to as plasma polymerization.<sup>3-5</sup> During a plasma polymerization, an electrical discharge taking place in an organic or inorganic gas, or mixture of gases, results in the formation of a thin polymer film on the surfaces exposed to the discharge. This technique originally seemed a solution to the problem of controlled fabrication of thin organic dielectric films. Initial hopes of rapid application of these films as dielectrics did not, however, materialize, because their characteristics degraded on aging and on exposure to moisture. These problems continue to inhibit the technological applications of these films.<sup>6</sup> We undertook investigations designed to improve the adhesion of plasma polymerized thin organic films to metal surfaces.

Initial investigations involved the coating of cleaned copper surfaces with plasma polymerized ethylene (PPE) in a Hummer X sputter coater.<sup>7</sup> The copper pieces were rectangles cut from copper sheet which had been cleaned with soap and water, distilled water, acetone and trichloroethylene, then etched with an argon plasma in the sputter coater immediately prior to use. The synthesis of the PPE thin films was accomplished by placing the substrate pieces on the lower horizontal electrode of the sputter coater. A target aluminum electrode was placed parallel to the lower electrode at a separation of 55 mm. The chamber was repeatedly evacuated and refilled with argon to remove contaminating gases, then evacuated and refilled three times with

ethylene.<sup>8</sup> An AC plasma (60 Hz) was created in the chamber of the sputter coater while maintaining an ethylene pressure of 100 mtorr. After 5 min the plasma was turned off, and the chamber was evacuated and slowly brought to atmospheric pressure by bleeding in argon. The resulting films were dark grey and insoluble in organic solvents and water. The advancing contact angle of distilled water on the film surface was  $\theta_a = 90-93^\circ$ , in good agreement with the reported values for polyethylene surfaces.<sup>9</sup> Qualitative test of the adhesion of the film to the copper surface, carried out by a peel test<sup>10</sup> with Scotch tape (3M-810), revealed that the films adhered well to the rough surface of the copper.

We next applied this technique to coating the surface of hand-polished copper disks.<sup>11</sup> The PPE films did not adhere to these polished surfaces. The films appeared intact until exposed to the room atmosphere, at which time they lost adhesion and flaked. This process was accelerated by breathing on the surface. These effects were independent of the type of copper that was used. We attempted to change the surface character of these polished copper disks, prior to coating with PPE, by treatment with aqueous chromium trioxide, aqueous sodium formate, dilute nitric acid, by electropolishing the disks in a 68% aqueous phosphoric acid solution, and by sputter coating the surface with thin layers of gold, silver and platinum, but found that all gave equally poor adhesion of the PPE thin film to the substrate. Mechanically roughening these surfaces produced the same film qualities (good adhesion) as was observed previously on the stock sheet copper surfaces. We therefore concluded that adhesion of the PPE film to the rough copper surfaces occurred mainly through sticking to surface asperities of size larger than about 3  $\mu\text{m}$ .<sup>12</sup>

Having failed in simple attempts to change the surface character of the copper to obtain better physisorption of the PPE thin film, we turned our

attention to modification of the surface using a designed adhesion promoter. Nuzzo and Allara<sup>13</sup> demonstrated that long hydrocarbon chain disulfides reacted with clean gold surfaces and gave chemisorbed organic monolayers in which the alkyl chains were fully extended with their longest axis largely perpendicular to the gold surface. These monolayers were stable at ambient conditions.<sup>13</sup> To make use of this monolayer technology in modifying the interphase between our copper substrate and the PPE thin films, we synthesized di- $\omega$ -docosenyldisulfide **1** (hereafter called the disulfide) by the reactions shown in Figure 1.<sup>14</sup> This long chain disulfide had a carbon-carbon double bond in the terminal position of its C<sub>22</sub> hydrocarbon chains. We hoped this double bond would bond covalently to the growing polyethylene chains produced in the glow discharge.

In our experiments the polished copper disks were first sputter coated with a thin film of gold and then soaked in a dilute solution of the disulfide in hexadecane for 12 hours. The disks were removed from the disulfide solution and carefully washed with hexane; their surface was oleophobic to hexane.<sup>15</sup> The disks were treated with the ethylene plasma. Plasma polymerization resulted in assembly of a composite thin film represented schematically in Figure 2. These films are deep blue in color and do not fail in the Scotch tape adhesion T test. They also survive cycling between room temperature and 77 °K (immersing in liquid nitrogen), and are unaffected by drops of acetone and water on their surface. Examination of the films with an optical microscope (100x) and with SEM (10000x) indicates that the films are pinhole free at that scale, and that they conform to surface irregularities in the metal stock. Examination of the films with ESCA (XPS) reveals a significant peak due to oxygen (either from reaction of radical centers on the film with dioxygen upon exposure to air at the completion of






Figure 1. Scheme of reactions for the synthesis of di- $\omega$ -docosenyldisulfide.




Figure 2. Schematic diagram of the surface in the various steps used for fabricating an insulating PE conformal coating.

the plasma polymerization process,<sup>1,6,16</sup> or from incorporation of oxygen from dioxygen or water, into the films during plasma deposition present as impurities in the vapor); no other element (other than carbon) is evident. The ESCA spectrum of these films shows no gold or sulfur, supporting the microscopic evidence that the thin films are free of macroscopic pinholes.

As a final step in fabrication of the thin film, we placed a gold electrode on its surface to test its electrical conductivity. The electrode was sputter coated onto the surface through a mask.<sup>17</sup> The resistivity of the film was carried out by attaching leads to the gold electrode region of the surface and to the copper disk: the resistance was greater than 1 megohm. These films have retained their properties on exposure to air for periods of over one year.

In conclusion, we have shown the adhesion of plasma polymerized polyethylene (PPE) thin films to a gold surface can be dramatically improved by coupling the synthesis of the PPE thin film with the prior assembly of an organic monolayer chemisorbed to the metal surface. These thin film assemblies have good physical characteristics and are stable to the ambient environment for long intervals. We believe this method should be applicable to other systems with appropriate modifications.

This research was supported by the Office of Naval Research, by the National Science Foundation (DMR 83-16979) and by the Department of Energy (DE-FG02-85ER45190). H.P.G. was an IBM postdoctoral fellow. K.R.S. was an NIH postdoctoral fellow (Grant No. HL-06897).

## References

- 1 A. M. Mearns, Thin Solid Films, 3 (1969) 201.
- 2 Y. Segui and B. Ai, Thin Solid Films, 50 (1978) 321.
- 3 A. T. Bell, J. Macromol. Sci. Chem., A10 (1976) 369. H. Yasuda, in J. L. Vossen and W. Kern (eds.), Thin Film Processes, Academic Press, 1978. M. Shen and A. T. Bell (eds.), Plasma Polymerization, ACS Symposium Series, 108, 1979. J. A. Thornton, Thin Solid Films, 107 (1983), 3.
- 4 C. S. Schoepfle and L. H. Connel, Ind. Eng. Chem., 21 (1929) 529. E. G. Linder and A. P. Davis, J. Phys. Chem., 35 (1931), 3649. H. Koenig and G. Helwig, Z. Physik., 129 (1951), 491. L. Holland, Brit. J. Appl. Phys., 9 (1958) 410. A. Brockes and H. Koenig, Z. Physik., 152 (1958) 75.
- 5 J. Goodman, J. Polymer Sci., 44 (1960) 551.
- 6 M. Gazieki and H. Yasuda, Plasma Chem. and Plasma Processing, 3 (1983) 279.
- 7 Hummer X Sputter Coater, Technics West Inc., San Jose, California.
- 8 Ethylene C. P. (99.5%), Matheson, Gloucester, Massachusetts.
- 9 A. W. Adamson, Physical Chemistry of Surfaces, Wiley Interscience, 1966, p. 349.
- 10 a) J. Strong, Rev. Sci. Instrum., 6 (1935) 97. b) R. Jacobsson and B. Kruse, Thin Solid Films, 15 (1973) 71. c) R. Jacobsson, Thin Solid Films, 34 (1976) 191.
- 11 Disks were made from electrolytic tough pitch copper (Copper Development Association Alloy Designation #110) or from oxygen free high conductivity copper (CDA #101). The disks were handpolished on a felt covered polishing wheel using aluminum oxide ( $Al_2O_3$ ) abrasive powder. The surfaces obtained in this manner had a surface roughness of approximately

0.15  $\mu$ , were hydrophilic and pink in color. Some disks showed "deep" scratches (10-100  $\mu$  deep) from machining. These were left in the surface to test the conformity of our coatings to surface irregularities. After polishing, the disks were cleaned ultrasonically with water and methanol to remove any weakly bound abrasive particles and then the disks were stored in methanol to prevent oxidation and keep the surface as clean as possible.

- 12 Surface roughness after electropolishing was  $\sim 3 \mu$  as measured by optical microscopy.
- 13 R. G. Nuzzo and D. L. Allara, J. Am. Chem. Soc., **105** (1983) 4481.
- 14 Reactions relevant to the synthesis are described in: D. E. Bergbreiter and G. M. Whitesides, J. Org. Chem., **40** (1975) 779. R. P. Volante, Tetrahedron Lett., **22** (1981) 3119.
- 15 W. C. Bigelow, D. L. Pickett and W. A. Zisman, J. Colloid Sci., **1** (1946) 513. J. Sagiv, J. Am. Chem. Soc., **102** (1980) 92.
- 16 A. R. Denaro, P. A. Owens and A. Crawshaw, Eur. Polymer J., **4** (1968) 93. M. Stuart, Nature, **199** (1963) 59.
- 17 K. L. Mittal, J. Vac. Sci. Technol., **13** (1976) 19.

### Captions

Figure 1. Scheme of reactions for the syntheis of di- $\omega$ -docosenyl disulfide.

Figure 2. Schematic diagram of the surface in the various steps used for fabricating an insulating PPE conformal coating.

## APPENDIX

DL/413/83/01  
GEN/413-2TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No. Copies</u>		<u>No. Copies</u>
Office of Naval Research Attn: Code 413 800 N. Quincy Street Arlington, Virginia 22217	2	Naval Ocean Systems Center Attn: Technical Library San Diego, California 92152	1
ONR Pasadena Detachment Attn: Dr. R.J. Marcus 1030 East Green Street Pasadena, California 91106	1	Naval Weapons Center Attn: Dr. A.B. Amster Chemistry Division China Lake, California 93555	1
Commander, Naval Air Systems Command Attn: Code 310C (H. Rosenwasser) Washington, D.C. 20360	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Naval Civil Engineering Laboratory Attn: Dr. R.W. Drisko Port Hueneme, California 93401	1	Dean William Tolles Naval Postgraduate School Monterey, California 93940	1
Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375	1	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12	Mr. Vincent Schaper DTNSRDC Code 2830 Annapolis, Maryland 21402	1
DTNSRDC Attn: Dr. G. Bosmajian Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Science Division San Diego, California 91232	1	Mr. A.M. Anzalone Administrative Librarian PLASTEC/ARRADCOM Bldg. 3401 Dover, New Jersey 07801	1

ABSTRACTS DISTRIBUTION LIST, 356B

Professor A. G. MacDiarmid  
Department of Chemistry  
University of Pennsylvania  
Philadelphia, Pennsylvania 19174

Dr. E. Fischer, Code 2853  
Naval Ship Research and  
Development Center  
Annapolis, Maryland 21402

Professor H. Allcock  
Department of Chemistry  
Pennsylvania State University  
University Park, Pennsylvania 16802

Professor R. Lenz  
Department of Chemistry  
University of Massachusetts  
Amherst, Massachusetts 01002

Professor M. David Curtis  
Department of Chemistry  
University of Michigan  
Ann Arbor, Michigan 48105

Dr. J. Griffith  
Naval Research Laboratory  
Chemistry Section, Code 6120  
Washington, D.C. 20375

Professor G. Wnek  
Department of Materials Science  
and Engineering  
Massachusetts Institute of Technology  
Cambridge, Massachusetts 02139

Mr. Samson Jennekke  
Honeywell Corporate Technology Center  
10701 Lyndale Avenue South  
Bloomington, Minnesota 55420

Dr. Richard M. Laine  
SRI International  
333 Ravenswood Avenue  
Menlo Park, California 94025

Dr. James McGrath  
Department of Chemistry  
Virginia Polytechnic Institute  
Blacksburg, Virginia 24061

Dr. Adolf Amster  
Chemistry Division  
Naval Weapons Center  
China Lake, California 93555

Professor C. Allen  
Department of Chemistry  
University of Vermont  
Burlington, Vermont 05401

Dr. William Tolles  
Code 6100  
Naval Research Laboratory  
Washington, D.C. 20375

Professor T. Katz  
Department of Chemistry  
Columbia University  
New York, New York 10027

Professor J. Salamone  
Department of Chemistry  
University of Lowell  
Lowell, Massachusetts 01854

Professor J. Chien  
Department of Chemistry  
University of Massachusetts  
Amherst, Massachusetts 01854

Professor William R. Krigbaum  
Department of Chemistry  
Duke University  
Durham, North Carolina 27706

Dr. R. Miller  
IBM Research Laboratory K42/282  
5600 Cottle Road  
San Jose, California 95193



ABSTRACTS DISTRIBUTION LIST, 356B

Professor T. Marks  
Department of Chemistry  
Northwestern University  
Evanston, Illinois 60201

Professor Malcolm B. Polk  
Department of Chemistry  
Atlanta University  
Atlanta, Georgia 30314

Dr. Kurt Baum  
Fluorochem, Inc.  
680 S. Ayon Avenue  
Azusa, California 91702

Professor H. Ishida  
Department of Macromolecular Science  
Case Western University  
Cleveland, Ohio 44106

Professor Stephen Wellinghoff  
Department of Chemical Engineering  
University of Minnesota  
Minneapolis, Minnesota 55455

Professor G. Whitesides  
Department of Chemistry  
Harvard University  
Cambridge, Massachusetts 02138

Dr. K. Paciorek  
Ultrasystems, Inc.  
P.O. Box 19605  
Irvine, California 92715

Professor H. Hall  
Department of Chemistry  
University of Arizona  
Tucson, Arizona 85721

END

DTIC

7-86